

### Remarks

This Preliminary Amendment cancels, without prejudice, claims 1-6 in the underlying PCT Application No. PCT/DE03/01806 and adds new claims 7-12. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and do not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/01806 includes an International Search Report, dated June 2, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

Applicants assert that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

Dated: 11/27/03

By: 

Richard L. Mayer  
(Reg. No. 22,490)

One Broadway  
New York, NY 10004  
(212) 425-7200

[10191/3739]

## CHILD SEAT AND METHOD FOR CHILD-SEAT DETECTION

### Background Information

~~The present invention is based on a child seat and a method for child-seat detection according to the definition of the species as set forth in the independent patent claims.~~

- 5 A transponder system for child-seat detection is known from the laid-open  
print German Patent Application No. DE 198 21 501 A1-501. This system utilizes  
radio signals to detect a child seat, the child-seat detection in the vehicle seat  
transmitting a radio signal to the transponder in the child seat, which then retransmits  
this signal in changed form. The child-seat identification is carried out on the basis of  
10 the retransmitted radio signal.

### Summary of the Of The Invention

- ~~In contrast, the~~ The child seat and the method for child-seat detection according to  
the present invention, ~~having the features,~~ have the advantage over the related art  
15 that they provide a simplified system for child-seat detection. It is distinguished in  
that a radio-identification module, which includes an identifier, is preferably  
introduced in the fabrics of the child seat. The radio-identification chip transmits a  
radio signal, which includes the identifier on the basis of which the child seat is  
detected, this transmission taking place continuously or intermittently, without any  
20 request. For that reason, the radio-identification chip is configured as transmitter  
module only and has no receiver structures. On the other hand, a receiver structure,  
but not necessarily a transmitter structure, is present in the vehicle seat. The radio  
identification according to the present invention is therefore achieved solely by a  
radio transmission from the child seat to the vehicle seat. Another advantage is that  
25 the simple, uncomplicated methodology applies to all child-seat manufacturers, so  
that a child seat specified by the vehicle manufacturer must not necessarily be  
purchased. Another advantage is that no intervention in the design of the child seat  
is required which, if necessary, also allows retroactive fitting using appropriate  
fabrics.

- 30 The vehicle may additionally include a conventional child-seat detection as it is  
known from the related art.

MARKED-UP VERSION OF SUBSTITUTE SPECIFICATION

EV323020341US

~~The measures and further refinements specified in the dependent claims allow advantageous improvements of the child seat and the method for child seat detection indicated in the independent claims.~~

5

It is particularly advantageous that the radio-identification chip is woven into the fabric itself. The radio-identification chip module may be bonded to the conductive web strips as it happens in wire-bonding methods. As an alternative, a flexible plastic foil, similar to a flexible circuit board, having attached connection pads may be used.

10

In both cases the radio-identification chip and the connecting region are hermetically encapsulated. The energy for the radio-identification chip in the fabrics may be provided either by an energy store such as a battery or an accumulator, which is rechargeable, or by a thermogenerator. Since the human body generates energy in

15

of this energy. Miniaturized thermogenerators, for instance, are able to obtain electrical energy from the temperature difference between the body surface and the ambient environment. Thermogenerators are simple electrical components made up of two different conductors or semiconductors. They are joined to one another at one end in each case and in this way form a thermo pair. If there is a temperature

20

difference between the two sides of a thermo pair, an electrical voltage will be generated due to the so-called Seebeck effect, and current will be able to flow through a connected load, which in this case is the radio-identification chip module.

25

A thermogenerator is made up of a multitude of thermo pairs, all of which are electrically interconnected in series and arranged side-by-side, in meander-shape, in order to ensure optimum space utilization. In this way, high overall voltages and electrical outputs are achieved. In contrast to batteries, these thermogenerators have very advantageous characteristics: They are washable, robust, they are made of environmentally friendly materials and have a practically unlimited service life. When

30

thermogenerators are implemented in textiles, it is important to select locations where the occurring temperature differences between the inside and outside are as high as possible. For a reliable, constant energy supply the generated temperature profiles at moderate ambient temperatures and with thin clothing must be taken into account. Relatively low temperature differences of four to six Kelvin are measured at the wrists, which generally have low skin temperature. In contrast, the neck region

35

reaches very high values. A collar in close contact with the skin generates temperature differences of 17 Kelvin, which makes this region very attractive for obtaining energy. However, this is in some respects not so attractive for a child seat. Nevertheless, the results generally indicate that temperature differences of at least 5 Kelvin are attained in the clothing, even at moderate ambient temperatures.

**MARKED-UP VERSION OF SUBSTITUTE SPECIFICATION**

To achieve the highest possible temperature difference across the thermogenerator, it must be integrated directly into the fabric and an excellent thermal transition to the skin has to be ensured. For its coupling to the outside, thin copper platelets in each case are affixed to its cold and hot side. Copper is particularly suitable due to the fact that it has very high thermal conductivity. To prevent the copper from discoloring the skin, it is also galvanically coated by a thin layer of gold or silver. The thermogenerator chip is encapsulated in a waterproof manner using polyurethane. The electrical contacts are connected to the silver-coated copper wires, which are insulated with the aid of polyester varnish and woven into the fabric. A buffer capacitor, which stores the generated energy, may be integrated directly at the thermogenerator or some other spot in the clothing. In the case of a temperature difference of 5 Kelvin across the thermogenerator chip made of silicon, an electrical power output of 1.0  $\mu$ watt per square centimeter is generated under a load and a no-load voltage of 10 volt per square centimeter. These values already suffice to supply a wristwatch with energy. Higher outputs may be obtained by higher temperature differences and a larger active surface. A power output of 10 to 300  $\mu$ watt is sufficient to supply medical sensors with energy and to transmit the data to a recording device in a wireless manner.

The child-seat detection according to the present invention may advantageously be combined with other methods for child-seat detection with the goal of achieving plausibility or increased reliability of the child-seat detection. For instance, it may be connected to a child-seat detection that determines the child seat via the seat-pressure profile, for example with the aid of a sensor mat, or which has an optical identification system for child-seat detection, i.e., a video sensor.

#### Brief Description of the Drawing Of The Drawings

~~Exemplary embodiments of the present invention are shown in the drawing and are elucidated in greater detail in the following description.~~

~~The figures show:~~

Figure 1 shows a first block diagram of the child seat according to the present invention;

Figure 2 shows a schematic representation of the device according to the present invention; ~~and~~

Figure 3 shows a flow chart of the method for child-seat detection according to the present invention.

5

~~Background of the Invention~~

#### Detailed Description

Apart from a direct mass determination in order to identify a child seat on the passenger side, there is the possibility of equipping the child seat with a transponder system. The so-called OC (occupant classification) mat includes a transmitter and receiver antenna. The child seat has at least one or a plurality of transponder coils, which react to the signal transmitted by the OC mat and return a corresponding signal, partially in encoded form. Via the receiver antenna it is then analyzed whether a child seat is located on the seat. Furthermore, it is ascertained on the basis of an identification what type of child seat is involved and how it is positioned.

According to the present invention, another method for the contact-less or contact-free detection or identification of child seats will now be introduced. In this context a method and a child seat are to be provided, which may be realized without major changes in the child seat itself. This allows every child-seat manufacturer to utilize the methodology of the transponder detection yet does not result in competitive distortions.

According to the present invention, a radio-identification chip, which will then emit an identifier for this particular child seat, is introduced into the fabrics of the child seat. The radio-identification chip has no receiver device and is supplied by its own energy supply, namely either a thermogenerator or an energy store such as a battery. It may be provided that the energy store be rechargeable or exchangeable. More than one radio-identification chip may be used in a child seat. The radio-identification chip is preferably woven into the textiles and is able to emit the radio signal on a permanent or intermittent basis. The method according to the present invention may be used in addition to other methods for child-seat detection such as analyzing a seat-pressure profile or an optical identification. This allows a plausibilization of these results.

Figure 1 shows a block diagram of the device of the present invention. In the child seat an energy store 1 is connected to a radio-identification chip 2. Via an output, radio-identification chip 2 is connected to an antenna 3. It is possible for all three components to be arranged on one element. They may also be separately

accommodated in the fabrics of the child seat. In the seat of the vehicle, an antenna 1 is connected to a receiver module 5, which is connected to a control unit 6. Control unit 6 is connected to an airbag control unit 7 to which a sensory system 9 is connected as well. Airbag control device 7 is connected to restraining means 8.

5

Radio-identification chip 2 uses energy from energy storage 1 for its operation, which is a thermogenerator or a battery, and in this way continuously transmits identification signals via radio communication using antenna 3. Such an identifier is received by antenna 4 and transmitted to receiver module 5, which performs signal conditioning via amplification, mixing and filtering. Receiver module 5 then transmits the identifier as digital signal to the control unit or to processor 6, which compares the received identifier with stored identifiers so as to ascertain whether it is an identifier emitted by a child seat. If a child seat was detected, control unit 6 transmits a signal to airbag control device 7 that a child seat is located on the seat in question. In this case, airbag control unit 7 will not trigger the respective restraining means. Otherwise, in a trigger case that is detected by sensory system 9 such as acceleration sensors, airbag control unit 7 would trigger restraining means 8 also for the seat on which the child seat is located.

20 The radio signal emitted by antenna 3 has only a limited range, so that other receivers in the vehicle, in particular for the other seats, are unable to receive this radio signal. This may be achieved by using a very high transmitting frequency, for example, or a very low transmitting capacity. In particular the weak transmission output is advantageous since it places a low load on energy store 1 and is also non-critical with respect to electromagnetic compatibility. The acceptance of such a radio-identification chip will also increase if the environmental impact of the emitted radio signals, and especially the effect on a small child seated in the child seat, are negligible.

30 Figure 2 shows a schematic representation of the device according to the present invention. A child seat 203 having the transmitter unit according to the present integrated into the fabric is arranged on a vehicle seat 201. Through contactless measurement 204 and with the aid of receiver 202, the vehicle seat detects the presence of a child seat on seat 201. This is recognized in the control unit ECU. The control unit ECU then transmits a corresponding signal to an airbag control unit AB-ECU checking whether the particular airbag is to be switched off or on. As a function thereof, airbag control unit AB-ECU then triggers restraining means 205.

Figure 3, in a flow chart, shows the sequence of the method for child-seat detection according to the present invention. In method step 301, radio-identification chip 2 transmits the identifier by means of a radio signal, with the aid of antenna 3. In method step 302, receiver 5, using antenna 4, receives this signal and transmits it to control unit 6. In method step 303, control unit 6 determines on the basis of the identifier whether a child seat is involved. If this is detected to be the case in method step 304, the airbag control unit will be triggered correspondingly in method step 306.

10 However, if it has been detected in method step 304 that no child seat is involved, the method is ended in method step 305.

Furthermore, this system offers the possibility of providing redundant information in addition to mass-determining sensors or pressure-foil sensors. The receive system on the vehicle side may just as well be integrated directly into the vehicle seat or into the seat back or the seat cover, in this way simplifying the mass production since the integration of foil-pressure sensors is very costly and may entail large tolerances during installation. An H-point increase is not given either since the characteristic of the fabric does not change. Another possible application is the integration of this electronics system in various seat pads. In the case of pressure foils, this results in blurring of the input signal. With appropriate identification it is possible to inform the control unit of this fact, and corresponding modifications may be made. This would prevent faulty classifications and possibly avoid de-energizing the airbag for persons as a result of faulty classifications.

25

The system according to the present invention preferably operates in the ISM frequency range or some other frequency range that is suitable for such short-range applications.

SummaryAbstract of The Disclosure

~~A~~In a child seat and a method for child-seat detection ~~are provided, which are distinguished in that,~~ a radio-identification chip, which is configured solely as a transmitter module, is introduced in the child seat, preferably in the fabric. Due to the automatically emitted radio signal, the child seat is detected by corresponding receiver devices in the vehicle.

(Figure 2)